

## STOCK RANGE OF ENCLOSURES IN RAL 7035 GREY WITH TRANSPARENT DOORS TO IP65

IP65 enclosures with transparent doors.

Rated voltage up to 690V and maximum current of 800A.

Made from HB ABS halogen-free material.

IP65 protection rating against solid objects and liquids.

IK08 degree of protection against mechanical impacts.

CE and RoHs marked.



PP3006

The PP range of IP65 enclosures with clear doors in various sizes. The enclosures in this series have a rated voltage up to 690V and are resistant to chemical agents, alkalis, oils, and salts. The maximum current of the units is 800A and they possess an operating temperature or between  $-35\text{ }^{\circ}\text{C}$  and  $+65\text{ }^{\circ}\text{C}$ . They are made from HB ABS halogen-free material and are mounted on a 1 mm galvanised steel mounting plate. All models are IP65 protected against solid objects and liquids and IK08 protected against mechanical impacts. The standard colour of the units is RAL 7035 (grey) with other colours available upon request. All types are CE and RoHs marked and available from stock.

Reference	Colour	Dimensions D x W x H (mm)	Weight (kg)
PP3011	RAL 7035 (grey)	130 x 200 x 300	1.80
PP3012	RAL 7035 (grey)	150 x 250 x 350	2.40
PP3014	RAL 7035 (grey)	170 x 300 x 400	3.00
PP3015	RAL 7035 (grey)	220 x 300 x 400	3.40
PP3016	RAL 7035 (grey)	190 x 350 x 500	4.35
PP3013	RAL 7035 (grey)	175 x 400 x 500	4.50
PP3017	RAL 7035 (grey)	240 x 400 x 500	5.40
PP3018	RAL 7035 (grey)	200 x 400 x 600	5.85
PP3020	RAL 7035 (grey)	250 x 500 x 700	9.70
PP3022	RAL 7035 (grey)	260 x 600 x 800	10.80